

FIXED LENS PLASTIC MINI-DOME CAMERA

DM-480IPE28



1/4" CMOS Sensor
 1.3 Mega-Pixel
 Min. Illumination: 0.5Lux
 ONVIF
 Digital WDR

3D Noise Reduction
 Motion Detection and Privacy Masking
 2.8mm Mega-Pixel Lens
 PoE Support

Specifications

Camera	Video	Model	DM-480IPE28
		Image Sensor	1/4" CMOS
		Effective Pixels	1280×720
		Electronic Shutter	1/25s ~ 1/100000s
		Day & Night	No
		Min. Illumination	0.5 lux
	Audio	Audio compression	No
		Communication	No
	Image Enhancement	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable
		WDR Range	Digital WDR
		Noise Reduction	3D-DNR
		Image Orientation	Mirror/Flip
		Privacy Zone	Yes
		Motion Detection	Yes
Compression	Video Compression	H.264	
	Resolution	720P (1280×720) ,D1 (704×567) ,CIF (480×240)	
	Multi-stream	1280x720 (1~30fps) D1 (1~30fps) / CIF (1~30fps)	
	Bit rate	64Kbps ~ 4Mbps	
	Encode Mode	VBR/CBR	
	Image Quality	Five levels under VBR; Free adjustment under CBR	

Housing	IR Distance	N/A
	Lens	2.8mm
	Iris	Fixed Iris
	Lens Mount	Φ12 mount
	Water-proof	No
	Bracket	2-Axis Gimbal
	Dimensions	Φ100mm×53mm
	Weight(gross)	592g
Connectivity	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	No
	Mic Connectivity	No
	SD Card	Support TF (64GB Max)
	RS485	No
Network	Alarm	No
	Remote Monitoring	IE Browsing, CMS Control Software
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
	ONVIF	Yes
Others	Ethernet	100Mbps
	PoE	Yes
Power Supply	Power Supply	DC12V/~130mA / PoE/~2.4W
	Work Environment	-10℃~50℃, 10%~90% Humidity

