

# IR VARI-FOCAL VANDAL-PROOF DOME CAMERA

DAI-331IP536



1/2.8" CMOS Sensor  
 3 Mega-Pixel  
 True Day & Night (IR Cut Removable)  
 0 Lux (IR On) Min. Illumination  
 Super Low Light Sensitivity  
 ONVIF

Digital WDR  
 3D Noise Reduction  
 Motion Detection and Privacy Masking  
 3.6mm Mega-Pixel Lens  
 15m IR Illumination  
 PoE Support

1 Way Audio  
 CVBS Output  
 IP 66 Protection  
 Vandal-Proof

## Specifications

Camera	Video	Model	DAI-331IP536
		Image Sensor	1/2.8" Sony CMOS
		Effective Pixels	2048×1536
		Electronic Shutter	1/25s ~ 1/100000s
		Day & Night	ICR
	Audio	Audio compression	G.711A/G.711U
		Communication	One-way Audio
	Image Enhancement	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable
		WDR Range	Digital WDR
		Noise Reduction	3D-DNR
Image Orientation		Mirror/Flip	
Privacy Zone		Yes	
Compression	Video Compression	H.265 / H.264	
	Resolution	3MP(2048×1536), 1080P(1920×1080), 720P(1280×720), D1, CIF, 480×240	
	Multi-stream	3MP(1~30fps) / 1920x1080(1~30fps) / 1280x720(1~30fps) D1(1~30fps) / CIF(1~30fps) / D1(1~30fps) / CIF(1~30fps) / 480x240(1~30fps)	
	Bit rate	64Kbps ~ 10Mbps	
	Encode Mode	VBR/CBR	
Image Quality	Five levels under VBR; Free adjustment under CBR		

Housing	IR Distance	15m (24 IR LED)
	Lens	3.6mm
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Water-proof	IP66
	Bracket	3-Axis Gimbal
	Dimensions	Φ116mm×91mm
	Weight(gross)	605g
	Network	RJ45 (+PoE)
	Power	DC Socket
Connectivity	Analog Video Output	CVBS (RCAX1)
	Mic Connectivity	1Ch Input
	SD Card	No
	RS485	No
	Alarm	No
Network	Remote Monitoring	IE Browsing, CMS Control Software
	User Access	Supports simultaneous monitoring for up to 10 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, PPPoE, DDNS, SMTP, FTP
	ONVIF	Yes
	Ethernet	100Mbps
PoE	Yes	
Others	Power Supply	DC12V/~440mA / PoE/~6.7W
	Work Environment	-10 C ~ 50 C, 10%~90% Humidity

