

# 1Ch HD Video Passive Balun

PTR-101V-HD+




MODEL		PTR-101V-HD+
Input		1Ch x Twisted Pair
Output		1Ch BNC
System Format		PAL / NTSC
Input Resolution Support		4MP and Lower
Input Signal Support		4 in 1 (AHD / CVI / TVI / CVBS)
Transmission Distance	4MP	200m (AHD) / 150m (CVI / TVI)
	2MP	200m (AHD) / 150m (CVI / TVI)
	1MP	200m (AHD) / 150m (CVI / TVI)
	960H and Lower	200m
Attenuation		1.5db Max
Wiring		Unshielded Twisted Pair
Surge Protection		2KV
Work Environment		-20°C-70°C, 0%-90% Humidity
Power Source		Not Required (Passive Unit)
Dimensions		Camera Side - 51x19x18mm / DVR Side - 40x20x18mm + 140mm Wire
Net Weight		30g

## Main Features:

- 1Ch Set
- 4MP 4in1 support: AHD / CVI / TVI / CVBS
- Passive - No Power Required
- Minimal Attenuation
- Light Weight

# 1Ch HD Video + Power Passive Balun

PTR-102VP-HD+



MODEL		PTR-102VP-HD+
Input		1Ch BNC + 12VDC Power
Output		1Ch BNC + 12VDC Power
System Format		PAL / NTSC
Input Resolution Support		4MP and Lower
Input Signal Support		4 in 1 (AHD / CVI / TVI / CVBS)
Transmission Distance	4MP	200m (AHD) / 150m (CVI / TVI)
	2MP	200m (AHD) / 150m (CVI / TVI)
	1MP	200m (AHD) / 150m (CVI / TVI)
	960H and Lower	200m
Attenuation		1.5db Max
Wiring		Cat5/5e/6 crimped cable (RJ-45)
Surge Protection		2KV
Work Environment		-20°C-70°C, 0%-90% Humidity
Power Source		Not Required (Passive Unit). Power is required for powered device only.
Dimensions		Camera/DVR Side - 73x29x20mm + 113mm Wire
Net Weight		60g

## Main Features:

- 1Ch Set
- 4MP 4in1 support: AHD / CVI / TVI / CVBS
- Passive
- Minimal Attenuation
- Light Weight

Power transmission max. distance

Model / Power Supply Consumption	DC 12V	DC 15V
200mA	180m	280m
300mA	120m	180m
400mA	100m	130m
500mA	80m	110m
600mA	60m	90m