



8CH PoE NVR

NVR5-8200PX

ossia



5MP



MODEL	NVR5-8200PX	
Video	Input	8CH RJ45 Direct Connection / Over Network
	Output	HDMI (1080P, 1280x1024)
	Decoding	H.265 / H.264
Audio	Input	Depends on Camera Inputs
	Output	1CH + Depends on Camera Outputs
	Two Way Audio	No
Bandwidth	Incoming	64Mbps
	Outgoing	64Mbps
Recording	Real-Time Recording	8CH 5MP Real-Time
	5MP	240FPS (NTSC)/200FPS (PAL)
	4MP	240FPS (NTSC)/200FPS (PAL)
	3MP	240FPS (NTSC)/200FPS (PAL)
	2MP (1080P)	240FPS (NTSC)/200FPS (PAL)
	1.3MP (960P)	240FPS (NTSC)/200FPS (PAL)
	1MP (720P)	240FPS (NTSC)/200FPS (PAL)
	960H	No
	D1	240FPS (NTSC)/200FPS (PAL)
	CIF	No
	Recording Modes	Schedule, Manual, Motion, Sensor
Playback	Playback Channels	8CH
	Search Mode	Time-Slice, Time, Event, File Management
Backup	USB	1 USB 2.0 Port
	DVD Burner	No
	Backup Format	AVI/DAT
Remote Application	Master Stream	Up to 8CH@Recording Resolution
	Sub-Stream	Depends on IPC
	Browser	IE, Safari, Firefox (Mac OS, Windows Vista/7/8/10)
	CMS	Yes
	Mobile Application	Provision CAM2 for iPhone/Android Phones/Tablets
	User Access	10 Users Online with Professional Authority Management
Alarm	Input	Depends on Camera
	Output	Depends on Camera
Storage	HDD	1 SATA (6TB)
	E-SATA	No
PTZ	Connection	Via Network
	Supported Controls	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus
	RS-485	No
Network	Ethernet	100 Mbps (RJ-45)
	Protocol	TCP/IP, DHCP, DDNS, NTP, SMTP, P2P, RTSP
	ONVIF	Yes
PoE	Ports	Yes (8CH)
	Interface	10/100Mbps
	Standard	IEEE802.3AF
	Total Power	120W (Average 12.5W per Channel)
	Max. Power Output (Per Ch.)	~14W
Others	Power Supply	DC48V/2.5A
	Power Consumption (No HDD)	5W
	Dimension	W300xD250xH50mm
	Operation Temperature	0°C ~50°C