


10M IR FIXED LENS BULLET CAMERA

I1-390IPS36



1/3" CMOS Sensor
 2 Mega-Pixel
 True Day & Night (IR Cut Removable)
 0 Lux (IR On) Min. Illumination
 ONVIF

Digital WDR
 3D Noise Reduction
 Motion Detection and Privacy Masking
 3.6mm Mega-Pixel Lens
 15m IR Illumination

PoE Support
 IP 66 Protection

Specifications

Camera	Video	Model	I1-390IPS36
		Image Sensor	1/3" CMOS
		Effective Pixels	1920x1080
		Electronic Shutter	1/25s ~ 1/100000s
		Frame Rate	1-25/30FPS
		Day & Night	ICR
		Min. Illumination	0lux (IR ON)
	Audio	Audio compression	No
		Communication	No
	Image Enhancement	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable
		Image Enhancement	Digital WDR, ROI
		Noise Reduction	3D-DNR
		Image Orientation	Mirror/Flip
		Privacy Zone	Yes
Motion Detection		Yes	
Compression	Video Compression	H.264	
	Resolution	1080P (1920x1080), 720P (1280x720), D1 (704x567), CIF (480x240)	
	Multi-stream	1920x1080 (1~30fps) / 1280x720 (1~30fps) D1 (1~30fps) / HD1 (480x240) CIF (1~30fps)	
	Bit rate	64Kbps ~ 10Mbps	
	Encode Mode	VBR/CBR	
	Image Quality	Five levels under VBR; Free adjustment under CBR	

Housing	IR Distance	15m (24 IR LED)
	Lens	3.6mm
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Protection Rate	Water Proof: IP66
	Bracket	3-Axis Wall Bracket
	Dimensions	70mm×70mm×155.8mm
	Weight(gross)	306g
Connectivity	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	No
	Mic Connectivity	No
	SD Card	No
	RS485	No
Network	Alarm	No
	Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP
	ONVIF	Yes
Others	Ethernet	100Mbps
	PoE	Yes
Power Supply	Power Supply	DC12V/~380mA / PoE/~6W
	Work Environment	-30 C~50 C, 10%~90% Humidity

