

30M IR BULLET WIRELESS CAMERA

I3-390WIP536*



- 2 Mega-Pixel camera
- Day & night vision
- 3.6mm lens with 80° Field of View
- Advanced H.265 Compression
- Wireless support
- 3D-DNR
- D-WDR
- Motion detection and Privacy Masking
- 12VDC Power Input

Specifications

Video	Model	I3-390WIP536
	Image Sensor	1/3" CMOS
	Effective Pixels	1920x1080
	Day & Night	ICR
	Min. Illumination	0lux (IR ON)
Audio	Audio compression	No
	Communication	No
Image Enhancement	Image Settings	AWB
		Auto Exposure Automatic Gain
		Saturation & Contrast Adjustable
	Noise Reduction	3D-DNR
	WDR Range	D-WDR
	Image Orientation	Mirror/Flip
	Privacy Zone	Yes
	Motion Detection	Yes
Compression	Video Compression	H.264/H.265
	Resolution	1080P (1920x1080)
	Multi-stream	1920x1080 (15fps) / 640x480 (15fps)
	Bit rate	128Kbps ~ 4Mbps
	Encode Mode	VBR/CBR
Pan/Tilt	Pan	No
	Tilt	No

Housing	IR Distance	30m (6pcs)
	Lens (Field of View)	3.6mm (80°)
	Iris	Fixed Iris
	Water-proof	Yes
	Bracket	Wall mount
	Dimensions	76x152 mm
	Weight(gross)	360g
Connectivity	Network	Wireless*
	Power	DC Socket
	Analog Video Output	No
	Audio Connectivity	No
	SD Card	No
	RS485	No
	Alarm	No
Network	Remote Monitoring	Provision CAM2 (Using NVR)
	User Access	Supports simultaneous monitoring for up to 3 users
	WPS	No
	ONVIF	No
	Ethernet	No
Others	PoE	No
	Power Supply	DC12V/~600mA
	Work Environment	-20°C~50°C, 10%~85% Humidity

*Must be paired with WR-01IPC / WR-04IPC adapting unit in order to work with Provision-ISR NVR

