

30M IR VARI-FOCAL BULLET CAMERA

I3-390HDVF
I3-380HDVF



1/3" CMOS Sensor
1080P / 720P
True Day & Night (IR Cut Removable)
0 Lux (IR On) Min. Illumination
WDR (at 15 fps) / Digital WDR

3D Noise Reduction
DSS (Digital Slow Shutter)
BLC/HLC
Motion Detection and Privacy Masking
2.8-12mm Vari-Focal Lens

30m IR Illumination
IP66
DC 12V

Specifications

MODEL	I3-390HDVF	I3-380HDVF
Image Sensor	1/3"CMOS	
Active Pixels	2010(H)×1092(V)	1305(H)×1049(V)
Lens	2.8-12mm Vari-Focal	
Scanning System	Progressive Scan	
Resolution	Digital:	1920x1080 (1080P 25/30FPS) 1280x720 (720P 25/30 FPS)
	Analog:	700TVL
Min. Illumination	0.0Lux (IR On) 34 IR LED Pieces	
IR Range	30m	
Video Output	Digital: HD-SDI (25/30FPS) Analog: NTSC/PAL	
True D&N	ICR (IR Cut Removable)	
S/N RATIO	>52dB (AGC Off)	
Sharpness	Adjustable	
Mirror/Flip	Yes	
D-Zoom	No	
HLC (Eclipse)	Off/On	
Brightness	Adjustable	
Lens	DC/Manual	
Shut Speed	Auto/Manual (1/60~1/67500)	
DSS(Sense-Up)	Off/ x2~x8	

MODEL	I3390HDVF	I3-380HDVF
AGC	Adjustable	
WDR/BLC	WDR (at 15 fps) / BLC / Off	D-WDR / BLC / Off
Day & Night	Auto / Day / Night / Ext	
Smart IR	Yes	
White BAL	ATW / Push / Indoor / Outdoor / Manual	
3D-DNR	Adjustable	
Privacy	Off/On (8 Areas)	
Motion	Off/On (4 Areas)	
Lens shading	Off/On	
System	NTSC/PAL	
HD Format	1080P	720P
COMM	No	
OSD	Available	
Power	DC 12V, 200mA (Max)	
Operating Temperature	-20 C ~ 50 C , (Humidity 10% ~ 90%RH)	
Dimension	Φ87(D) ×219(H) mm	
Weight	635g	
IP Rating	IP66	

