

4 CH AHD + 1 CH IP Hybrid DVR

SA-4050AHD-2+

1080P Lite 1080P

1080P



| | | | |
|---------------------------|--|--|--|
| MODEL | | SA-4050AHD-2+ | |
| System | Compression Format | High profile H.264 | |
| | ONVIF | Yes | |
| | Format | Tribrid AHD / TVI / CVBS + IP | |
| Video | Input | 4CH Standard BNC + 1CH IP (Over Network) | |
| | Standard Output | HDMI, VGA (800x600, 1024x768), CVBS(Spot) | |
| Audio | Input | 4CH | |
| | Output | 1CH | |
| | Two Way Audio | Yes | |
| Recording | AHD + TVI | Real-Time Recording | 4CH 1080P Half Real-Time |
| | | 2MP (1080P) | 60FPS (NTSC)/50FPS (PAL) Total. Up to 15/12FPS Per Channel |
| | | 2MPL (1080P Lite) | 120FPS (NTSC)/100FPS (PAL) |
| | | 1MP (720P) | 120FPS (NTSC)/100FPS (PAL) |
| | Analog | Real-Time Recording | 4CH 960H Real-Time |
| | | 960H | 120FPS (NTSC)/100FPS (PAL) |
| | | D1 | No |
| | | CIF | No |
| | IP | Real-Time Recording | 1CH 1080P Real-Time |
| | | 3MP | No |
| | | 2MP (1080P) | 30FPS (NTSC)/25FPS (PAL) |
| | | 1.3MP (960P) | 30FPS (NTSC)/25FPS (PAL) |
| | | 1MP (720P) | 30FPS (NTSC)/25FPS (PAL) |
| General | Recording Modes | Schedule, Manual, Motion, Sensor | |
| Playback | AHD/TVI/CVBS Playback | 4CH | |
| | IP Playback | 1CH | |
| | Search Mode | Time, Event, File Management | |
| Backup | USB | 2 USB 2.0 Port | |
| | DVD Burner | No | |
| | Backup Format | AVI/DAT | |
| Remote Application | AHD Stream | Master Stream 1-25/30FPS@720P / 1-12/15FPS@1080P; Sub-Stream: Up to 1-25FPS@720P | |
| | Analog Stream | Master Stream 1-25/30FPS@960H; Sub-Stream Up to 1-25FPS@960H | |
| | IP Stream | Master Stream 1-25/30FPS@1080P; Sub-Stream Up to 1-25/30FPS@D1 | |
| | Master Stream | Up to 4Ch@Recording Resolution | |
| | Browser | E, Safari, Firefox (Mac OS, Windows XP/Vista/7/8) | |
| | CMS | Yes | |
| | Mobile Application | Provision Cam2 for iOS/Android | |
| User Access | 10 Users Online with Professional Authority Management | | |
| Alarm | Input | 4CH | |
| | Output | 1CH | |
| Storage | HDD | 1 SATA (6TB) | |
| | E-SATA | No | |
| PTZ | Connection | RS-485 / CoC / IP-Over Network | |
| | Supported Protocols | Pelco D, Pelco P, Samsung, Visca, ONVIF, CoC | |
| | Supported Controls | Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus | |
| Network | Ethernet | 100 Mbps (RJ-45) | |
| | Protocol | TCP/IP, DHCP, DDNS, NTP, SMTP, P2P | |
| Others | Dimention | W300xD250xH45mm | |
| | IR Controller | Yes | |
| | Power Supply | 12V/2A | |
| | Operation Temperature | 0°C ~50°C | |